



Lager Nr.	DICHTUNGSTYP	Bohrungsdurchmesser (d)	Außendurchmesser (D)	Breite (B)	KUGELGRÖSSE (mm)	KUGELMENGE	Gewicht (g)
682	open	2	5	1.5	0.8	6	0.15
682zz	Shield	2	5	2.3	0.8	6	0.2
682-2RS	Rubber seal	2	5	2.3	0.8	6	0.2
MR52	open	2	5	2	0.8	6	0.14
MR52ZZ	Shield	2	5	2.5	0.8	6	0.2
MR52-2RS	Rubber seal	2	5	2.5	0.8	6	0.2
692	open	2	6	2.3	1.2	6	0.28
692ZZ	Shield	2	6	3	1.2	6	0.35
692-2RS	Rubber seal	2	6	3	1.2	6	0.35
MR62	open	2	6	2.5	1.2	6	0.28
MR62ZZ	Shield	2	6	2.5	1.2	6	0.33
MR62-2RS	Rubber seal	2	6	2.5	1.2	6	0.33
MR72	open	2	7	2.5	1.2	7	0.43
MR72ZZ	Shield	2	7	3	1.2	7	0.53
MR72-2RS	Rubber seal	2	7	3	1.2	7	0.53
602	open	2	7	2.8	1.2	7	0.5
602ZZ	Shield	2	7	3.5	1.2	7	0.6
602-2RS	Rubber seal	2	7	3.5	1.2	7	0.6
MR63	open	3	6	2	0.8	8	0.2
MR63ZZ	Shield	3	6	2.5	0.8	8	0.28
MR63-2RS	Rubber seal	3	6	2.5	0.8	8	0.28
683	open	3	7	2	1	8	0.32
683ZZ	Shield	3	7	3	1	8	0.45
683-2RS	Rubber seal	3	7	3	1	8	0.45
MR83	open	3	8	2.5	1.2	7	0.51
MR83ZZ	Shield	3	8	3	1.2	7	0.67



## Ceramic Hybrid Ball Bearings

MR83-2RS	Rubber seal	3	8	3	1.2	7	0.67
693	open	3	8	3	1.2	7	0.6
693ZZ	Shield	3	8	4	1.2	7	0.8
693-2RS	Rubber seal	3	8	4	1.2	7	0.8